

DATENBLATT - skyjack – Scherenbühne SJ 6832 RTE

Dimensions	SJ6832 RTE
A Work Height	38' (11.58 m)
B Raised Platform Height	32' (9.75 m)
C Lowered Platform Height	54" (1.37 m)
D Overall Width	69.5" (1.76 m)
E Overall Length	107" (2.72 m)
F Stowed Height (Rails Up)	99" (2.51 m)
G Stowed Height (Rails Down)	69" (1.75 m)
H Platform Width (Inside Dimension)	56" (1.42 m)
I Platform Length (Inside Dimension)	96" (2.44 m)
Specifications	SJ6832 RTE
Extension Deck	5' (1.52 m)
Ground Clearance	8" (0.20 m)
Wheelbase	80.5" (2.04 m)
Weight	7,885 lbs (3,577 kg)
Gradeability	45%
Turning Radius (Inside)	60" (1.52 m)
Turning Radius (Outside)	156" (3.96 m)
Lift Time (With Rated Load)	39 sec
Lower time (With Rated Load)	36 sec
Drive Speed (Stowed)	3.5 mph (5.6 km/h)
Drive Speed (Raised)	0.4 mph (0.6 km/h)
Maximum Drive Height	Full Height
Capacity (Overall)	1,000 lbs (454 kg)
Distributed Capacity (Main Platform)	700 lbs (318 kg)
Distributed Capacity (Extension Deck)	300 lbs (136 kg)
Local Floor Load (With Rated Load)	184 psi (1269 kPa)
Overall Floor Load (With Rated Load)	281 psf (13 kPa)
Maximum # of Persons	4
Tire Type	Foam Filled Non-Marking
Tire Size	26 x 12

Weitere Informationen

Landshut 08703 988168

München 089 54507739

Regensburg 0941 5997150

Angaben ohne Gewähr

Quelle Hersteller

